Negative Pressure Protective Isolator

负压防护隔离器

Product Introduction 产品简介

设备全密闭，运行时维持负压，主要用于处理有毒原料、高致敏性和激素类物料，目的在于保护操作人员或者环境免受其影响，可保证物料和人员的隔离，实现物料生产过程中对操作人员的有效保护。

The equipment is fully enclosed and maintains negative pressure during operation. It is mainly used to handle toxic raw materials, highly sensitized and hormonal materials. The purpose is to protect operators or the environment from their impact, ensure the isolation of materials and personnel, and achieve effective protection for operators during the production of materials.

Product Advantages 产品优势

设备在客户现场经过第三方验证，可以满足OEB5级标准；

The equipment has been verified by a third party at the customer's site and can meet the OEB5 standard;



自动程序控制，PID界面显示，实现电子签名、数据报表、历史曲线、审计追踪和历史报警等多重数据分析处理；

Automatic program control, PID interface display, multiple data analysis and processing such as electronic signature, data report, historical curve, audit tracking and historical alarm;

重复打印可以对上次运行数据进行多次打印，防止因为打印纸用尽或打印机损坏造成打印数据丢失；

Repeated printing can print the last operation data for many times to prevent the loss of printing data due to the exhaustion of printing paper or the damage of the printer;

选用直流风机，PID自动控制，压差控制稳定；

DC fan is selected with PID automatic control and stable differential pressure control;



配置PUSH-PUSH双级安全更换过滤器，满足安全更换要求；

Equipped with PUSH-PUSH two-stage safety replacement filter to meet the safety replacement require-ments;

配置有水气两用喷枪，用于生产结束后设备的清洁；

Equipped with a dual-use spray gun for cleaning equipment after production;

配置袋出装置或RTP，用于剩余物料或废弃物的处理。

Bag out device or RTP shall be configured for disposal of surplus materials or wastes.